

Torch Ordering Information

Model	Head Type	Length	Part No.	Current Rating	Coolant Requirements	Torch Dimensions					
						A	B	C		D	E
P15-H	70 degree	12.5 ft.	P15-1000	150 Amps	6K BTU/Hr (1513 K/Cal/hr) 1/3 gpm coolant flow @ 50 psi (1.25 lpm @ 3.7 kg/cm ²)	8-3/4"	2-5/8"	7/8"		1-1/16"	
P15-H	70 degree	25 ft.	P15-1001			(222 mm)	(67 mm)	(22 mm)		(27 mm)	
P15-H	90 degree	12.5 ft.	P15-1002			8-1/2"	2-5/8"	7/8"		1-1/16"	
P15-H	90 degree	25 ft.	P15-1003			(216 mm)	(67 mm)	(22 mm)		(27 mm)	
P15-M	180 degree offset, R&P	12.5 ft.	P15-1004			19-1/4"	1"	Min.	Max.	1-3/8"	
P15-M	180 degree offset, R&P	12.5 ft.	P15-1005			(489 mm)	(25 mm)	9-1/4"	16-3/4"	(35 mm)	
P15-M	180 degree offset, R&P	25 ft.	P15-1006					(235 mm)	(425 mm)		
P15-M	180 degree offset, R&P	25 ft.	P15-1007								
P22-H	70 degree	12.5 ft.	P22-1000	220 Amps	8K BTU/Hr (2017 K/Cal/Hr) 1/2 gpm coolant flow @ 50 psi (1.9 lpm @ 3.7 kg/cm ²)	12-1/2"	3-3/16"	1-1/4"		1-3/8"	
P22-H	70 degree	25 ft.	P22-1001			(318 mm)	(81 mm)	(32 mm)		(35 mm)	
P22-H	90 degree	12.5 ft.	P22-1002			12-1/2"	3-3/16"	1-1/4"		1-3/8"	
P22-H	90 degree	25 ft.	P22-1003			(318 mm)	(81 mm)	(32 mm)		(35 mm)	
P22-H	180 degree inline	12.5 ft.	P22-1006			21"	1-3/4"	1-1/4"		1-3/8"	
P22-H	180 degree inline	25 ft.	P22-1007			(533 mm)	(44 mm)	(32 mm)		(35 mm)	
P22-M	180 degree offset, R&P	12.5 ft.	P22-1004			18"	1-3/4"	8-1/4"	16"	1-3/8"	1-1/4"
P22-M	180 degree offset, R&P	25 ft.	P22-1005			(457 mm)	(44 mm)	(209 mm)	(406 mm)	(35 mm)	(32 mm)
P22-M	180 degree inline, R&P	12.5 ft.	P22-1008	21"	1-3/4"	11-1/4"	19"	1-3/8"	1-1/4"		
P22-M	180 degree inline, R&P	25 ft.	P22-1009	(533 mm)	(44 mm)	(286 mm)	(483 mm)	(35 mm)	(32 mm)		
P30-M	180 degree inline, R&P	12.5 ft.	P30-1000	300 Amps	12K BTU/Hr (3025 K/Cal/Hr) 3/4 gpm coolant flow @ 100 psi (1.9 lpm @ 3.7 kg/cm ²)	22-3/16"	2-1/2"	Min.	Max.	1-3/8"	1-5/8"
P30-M	180 degree inline, R&P	25 ft.	P30-1001			(.56 m)	(64 mm)	8-1/4"	16"	(35 mm)	(41 mm)
P30-M	180 degree inline, R&P	50 ft.	P30-1002					(209 mm)	(406 mm)		

Note: H designates torch with molded handle, M designates torch with rack and pinion assembly.

